

Cold Drawer Metos Classic GR-2000-GN2L-GN2L-GN2L-GN2L-MU



Product information

SKU	4334036S
Productnaam	Cold Drawer Metos Classic GR-2000-GN2L-GN2L-GN2L-GN2L-MU
Afmetingen	2000 × 650 × 650 mm
Gewicht	130,280 kg
Technical information	220-240 V, 10 A, 0.53 kW, 1NPE, 50 Hz
Energy class	D Energy class certificate
Type of the refrigerant	R290A
Quantity of refrigerant [g]	92

Description

Metos Classic GR-2000-GN2L-GN2L-GN2L-GN2L-MU grill drawer counter's height is 650 mm, which allows placing grill units on the top of the counter. Metos Classic refrigeration and dispensing equipment are designed for different purposes of the professional kitchens and can function as separate units as well as the complete sets of distribution lines.

Lowered Metos Classic GR-2000-GN2L-GN2L-GN2L-GN2L-MU grill drawer counter has drawers eight GN1/1-150 containers. Over extension telescopic slides enable the easy replacement of the GN-containers as



well as the flawless and quick opening and closing of the drawers.

The top surface of the grill drawer counter is well insulated, which prevents the heat from the grilling devices from reaching the cold spaces. The temperature adjustment range of the refrigerator is from +3°C to +10°C. The cast urethane insulation keeps the cool air inside the device and the efficient cooling fan distributes the air evenly all over the drawer. This cold drawer counter has an electronic control with a digital temperature display. The control panel is retracted and thus protected from any collisions.

Hygienic stainless steel countertop's rounded corners and tool-free removable drawer slides make it easy to clean the grill drawer counter. Removable and washable filter at the front part of the condenser keeps the cool air inside the device clean and at the same time prevents the device from getting dirty. The device has an automatic defrosting and evaporation of the meltwater, as well as a standard drainage possibility. The sealing gaskets of the drawers can be replaced without any tools. Grill drawer counter is supplied with connectors for power cables at the bottom of the device, making it easier to keep the floor under the device clean.

- the height of the device is 650 mm
- capacity 8xGN1/1-150 drawers (GN-containers are not included in the delivery)
- over extension telescopic slides
- temperature adjustment range is +3°C... +10°C
- digital temperature screen
- electronic control
- stainless steel structure
- cast urethane gasket
- removable and washable condenser filter
- automatic defrosting and evaporation of meltwater
- easy-to-change gaskets
- nondetachable refrigerator at the right side of the device
- adjustable feet +20...-45 mm
- refrigerant R290

THE DELIVERY INCLUDES:

- connectors for power cables

ACCESSORIES (to be ordered separately):

- GN containers
- bottom panel for the drawer
- drawer's internal frame for GN-containers of different sizes