

## Water softener Metos Bestsoft 11



### Product information

---

SKU	4136566
Productnaam	Water softener Metos Bestsoft 11
Afmetingen	270 × 480 × 532 mm
Gewicht	10,000 kg
Capacity	1440 litres/hour
Technical information	230 V, 0,15 kW, , 50 Hz CW: 3/4"

### Description

Protects machines optimally from calcification. Simplex soft water plant in compact design. Fully automatic and simple to operate. More output and less salt consumption by proportional salting process. Prefabricated and assembled in the factory for simple installation and start-up. Extended digital control system for maximum performance and efficiency. Rotary valve for higher safety for operations.

- 1 bar pressure loss at nominal flow according to EN14743
- 10 l of ion exchange resins
- 26 m<sup>3</sup>/°dH nominal capacity
- 4,5 mol nominal capacity
- reserves 12kg of regenerating agent in the cabinet
- 1,5kg salt consumption per regeneration
- 85 l water consumption per regeneration
- Temperature of water (min./max.) 5°C/30°C
- temperature of surrounding (min./max.) 5°C /40°C



- 403 mm connection height for hard water inlet and soft water outlet
- DN50 channel connection (min.)
- operative weight, approx. kg 40

Accessories( sold separately)

- salt
- sanitabs