

Cold display Metos Gastro OE-145-87-E



Product information

SKU	4000231
Productnaam	Cold display Metos Gastro OE-145-87-E
Afmetingen	1450 × 695 × 870 mm
Gewicht	240,000 kg
Technical information	230 V, 10 A, 1,077 kW, 1NPE, 50 Hz
Type of the refrigerant	R404A

Description

Metos Gastro OE-145-87-E is a recessed, self-service chilled display designed for use under demanding conditions, with a width of 1450 mm and height of 870 mm. The simple angular shape of the chilled display highlights the products being sold.

The display's tempered glass side panels, the glass shelf and the bright LED lighting for shelves and the cold tub make products being sold highly visible. The self-service display is temptingly open on the customer side, with a hinged glass door on the seller's side. The glass shelf can be regulated +/-25 mm and can be angled, which simplifies product selection. A 215 mm adjustable height cooled tub with Gastronorm dimensioning.

A great deal of attention has been paid to simplifying the cleaning of the Metos Gastro OE-145-87-E display. The display portion lacks virtually any seams and is easy to wipe clean. The tub's bottom plates,



which are made of stainless steel, can be removed and lifted up in order to clean the evaporator element. In addition, the display is equipped with an auto-defrost function, the melting water from which is directed to the grey water system. For those installation locations where it is not possible to connect the display to the grey water system, an evaporation tank is included as an accessory.

The display is equipped with air cooled chilling, digital temperature control and a fan speed regulator. Temperature can be regulated between +4 °C...+12 °C. The glass side panels and glass shelf are made from tempered glass. The substructure is made from stainless steel and insulation is polyurethane.

- display with air curtain
- recessable into furniture (cut out size 1390 x 670 m)
- shelf and tub lighting
- tempered glass side panels and shelf
- sales space 1,9 m²
- temperature can be regulated between +4 °C...+12 °C.
- climate class 3M2
- digital temperature regulation
- ventilator speed regulator

EXTRA ACCESSORIES (can be ordered separately):

- base; MG4321368 (Open stand), MG4000230 (Tubular body stand)
- sneeze guard for shelf
- price tag frame;
- bread frame;
- ancillary space;
- door locking;
- evaporation tank; MG4231377 (Manual), MG4231373 (Electrical 1000 W)
- central motor model.